



Sprayer with tangential blower

Characteristics:

- Blowing group with a width of only 480 mm.
- High air performance, with little power requirement.
- Optimal air distribution over the whole height, drift reduction.
- Blower and jets are switched on electrically and parallel.
- Automatical filter washing.
- The blower has a low weight, light construction of coated aluminium and stainless steel.
- Expandable to a recycling sprayer.

Models	G20T	G22T	G30T	G20TV	G22TV	G30TV
Tank (l)	200	250	300	200	250	300
Washing tank (l)	-	30	70	-	30	70
Fresh water tank (l)	10	10	10	10	10	10
Tangential blowers	2	2	2	2	2	2
Air performance (m ³ /h)	2x7000	2x7000	2x7000	2x7000	2x7000	2x7000
Height blower (mm)	1500	1500	1500	1500	1500	1500
Single blower height-adjustable	no	no	no	yes	yes	yes
Max. height blower	2.000	2.000	2.000	3.000	3.000	3.000
Hydraulic control	yes	yes	yes	yes	yes	yes
Oil requirement (l)	16	16	16	16	16	16
Pump 3 membranes	1	1	1	1	1	1
Performance (l/min)	50	50	80	50	50	80
Max. pressure (bar)	40	40	40	40	40	40
Double wave jets	10	10	10	10	10	10
Electrical control	yes	yes	yes	yes	yes	yes
Empty weight (kg)	150	155	160	165	170	175



* Technical modifications reserved.