



GEIER

Tunnel sprayer with recycling system

Characteristics:

- Compact blowing group with collecting and recycling system.
- High air performance, with little power requirement.
- Optimal air distribution over the whole height, drift reduction.
- Blower and jets are switched on electrically and parallel.
- Automatical filter washing.
- The blower has a low weight, light construction of coated aluminium and stainless steel.
- The blowing group is swivelling, for the use on both sides.

Models	G30UR	G22UR
Tank (l)	300	250
Washing tank (l)	70	30
Fresh water tank (l)	10	10
Tangential blowers	2	2
Air performance (m ³ /h)	2x7000	2x7000
Height blower (mm)	1500	1500
Hydraulic control	yes	yes
Oil requirement (l)	14	14
Pump 3 membranes	1	1
Performance (l/min)	80	50
Max. pressure (bar)	40	40
Jets	10	10
Electrical control	yes	yes
Recycling pump electrical (l/min)	2x 13	2x 13
Possibility of adjustment of the blowing group:		
Height up – down (m)	0,5	0,5
Angle of inclination	yes	yes
Swivelling left or right side	yes	yes
Width adjustment (m)	0,7- 1	0,7- 1
Empty weight (kg)	350	340

* Technical modifications reserved



GEIER GmbH/Srl, Einpersonengesellschaft/ unico socio

Neuwiesenweg 13, Via Prati Nuovi, I-39020 Marling / Marleno (BZ) · Tel. +39 0473 442260 · Fax +39 0473 200141 · info@geier.it · www.geier.it